

ENGINE	1.6 Multijet Diesel 1.598cc 120hp MT 4X2
No. of cylinders, layout	4 – in line
Displacement (cm ³)	1.598
Bore x stroke (mm)	79,5 x 80,5
Valves per cylinder	4
Compression ratio	16,5:1
Maximum power in kW @ rpm	88,3 kW @ 3.750 rpm
Max torque in Nm @ rpm	320 Nm @ 1.750 rpm
Injection system	Multi-Jet II common rail with electronic high-pressure injection
Fuel type	Diesel
TRANSMISSION	
Transmission	6-speed manual
1a	4,151
2a	2,118
3a	1,361
4a	0,978
5a	0,756
6a	0,622
Reverse	4,000
PERFORMANCE	
Acceleration: 0-100 km/h (s)	10,2
Top speed (km/h)	178
CONSUMPTION AND EMISSIONS	
Emission standard	Euro 6D-TEMP
Fuel consumption – combined cycle (l/100km)	4,6 – 4,7
Fuel consumption – extra-urban cycle (l/100 km)	4,0 – 4,2
Fuel consumption – urban cycle (l/100 km)	5,5 – 5,6
CO ₂ emissions – combined cycle (g/km)	121 - 123
Fuel tank (litres)	55
Urea tank (litres)	13
Urea range (km)	10.000 – 15.000
WEIGHTS AND DIMENSIONS	
STD kerb weight. A (kg)	1.430
Weight distribution between front/rear (%)	61,1 / 38,9
Height (mm)	1.667
Width (mm)	1.805
Length (mm)	4.236
Wheelbase (mm)	2.570

Ground clearance	175
Cargo volume (l) with seats up	351
Cargo volume (l) with rear seats folded	1.297

OTHER	
Turning circle (m)	11,07
„,Steering ratio	53,7 mm/g

