

ENGINE	<u>1.6L Multijet Diesel 1.598cc 120hp MT 4X2</u>
No. of cylinders, layout	4 in line
Displacement (cm3)	1.598
Bore x stroke (mm)	79,5 x 80,5
Valves per cylinder	4
Compression ratio	16,5:1
Maximum power in kW @ rpm	88 kW @ 3.750 rpm
Max torque in Nm @ rpm	320 Nm @ 1.750 rpm
Injection system	Multi-Jet II common rail with electronic high-pressure injection
Fuel type	Diesel
TRANSMISSION	
Transmission	6-speed manual
1a	4.154
2a	2.118
3a	1.361
4a	0.978
5a	0.756
6a	0.622
Reverse	4
PERFORMANCE	
Acceleration: 0-100 km/h (s)	11,0
Top speed (km/h)	185
CONSUMPTION AND EMISSIONS	
Emission standard	Euro 6D-TEMP
Fuel consumption – combined cycle (l/100km)	4,8
Fuel consumption – extra-urban cycle (l/100 km)	4,1
Fuel consumption – urban cycle (l/100 km)	6,3
CO2 emissions – combined cycle (g/km)	134
Fuel tank (litres)	60
Urea tank litres)	13
Urea range (km)	10.000 – 15.000
WEIGHTS AND DIMENSIONS	
STD kerb weight. A (kg)	1.615
Weight distribution between front/rear (%)	
Height (mm)	1.624
Width (mm)	1.819
Length (mm)	4.394
Wheelbase (mm)	2.636

Ground clearance	198
Cargo volume (l) with seats up	438
Cargo volume (l) with rear seats folded	1.251
OTHER	
Turning circle (m)	11,07
Steering ratio	15,6:1