

<b>ENGINE</b>	<b>Wrangler Unlimited Sahara 4-door petrol 2.0L TC GME ATX 4WD</b>
No. of cylinders, layout	4 – in line
Displacement (cm <sup>3</sup> )	1995
Bore x stroke (mm)	84.0 x 90.0
Valves per cylinder	4
Compression ratio	10:01
Max. power kW @ rpm	200 kW @ 5.250
Max. torque Nm @ rpm	400 Nm @ 3.000
Fuel injection	Gasoline Direct Injection
Fuel type	PETROL
Fuel tank capacity (l)	81
<b>GEARBOX</b>	
Transmission	8-speed AUTOMATIC
1 <sup>st</sup>	4.714
2 <sup>nd</sup>	3,143
3 <sup>rd</sup>	2.106
4 <sup>th</sup>	1.667
5 <sup>th</sup>	1.285
6 <sup>th</sup>	1.000
7 <sup>th</sup>	0.839
8 <sup>th</sup>	0.667
Reverse	3.295
Final drive ratio	3.45
<b>DRIVETRAIN</b>	
Transfer case	Command-Trac Low gear 2.72:1
Crawl ratio	44.2

<b>PERFORMANCE</b>	
Acceleration: 0-100 kph (s)	7.6
Top Speed (kph)	180
<b>CONSUMPTION AND EMISSIONS (NEDC -2)</b>	
Emission standard	EU6D- TEMP
Fuel consumption –urban (l/100 km)	11
Fuel consumption –extra-urban (l/100 km)	7.5
Fuel consumption –combined (l/100 km)	9
CO <sub>2</sub> emissions –urban (g/km)	-
CO <sub>2</sub> emissions –extra-urban (g/km)	-
CO <sub>2</sub> emissions –combined (g/km)	201

<b>WEIGHT AND DIMENSIONS</b>	
Kerb weight STD. A (kg)	2037
Weight distribution front/rear (%)	53/47
Max. payload (kg)	526
Height (mm) w/ standard soft top	1891
Width (mm)	1.894
Length (mm)	4.882
Wheelbase (mm)	3.008
Ground clearance (mm)	242
Load capacity (l) with seats in position	548
Load capacity (l) with flat rear seats	1059

<b>OTHER</b>	
Approach/departure/breakover angle	35.4/30.7/20.0
Turning Diameter (m)	12,28
Steering angle (inner/outer wheel)	41°/34.4°
Steering Turns	3.24
Steering ratio	14.2
Water fording (mm/kph)	760/8