ENGINE	Wrangler Sahara 2-door petrol 3.6 ATX 4WD 285 hp
No. of cylinders, layout	6 – in line
Displacement (cm ³)	3605
Bore x stroke (mm)	96.0 x 83.0
Valves per cylinder	4
Compression ratio	11.3:1
Max. power kW @ rpm	209 kW @ 6.400
Max. torque Nm @ rpm	347 Nm @ 4.100
Fuel injection	Port fuel Injected
Fuel type	PETROL
Fuel tank capacity (I)	66
GEARBOX	
Transmission	8-speed AUTOMATIC
1 st	4.714
2 nd	3,143
3 rd	2.106
4 th	1.667
5 th	1.285
6 th	1.000
7 th	0.839
8 th	0.667
Reverse	3.295
Final drive ratio	3.45
DRIVETRAIN	
Transfer case	Command-Trac Low gear 2.72:1
Crawl ratio	44.2

PERFORMANCE		
Acceleration: 0-100 kph (s)	-	
Top Speed (kph)	177	
CONSUMPTION AND EMISSIONS*		
Emission standard	EU6B	
Fuel consumption – urban (I/100 km)	13	
Fuel consumption – extra-urban (I/100 km)	7.7	
Fuel consumption – combined (I/100 km)	9.6	
CO ₂ emissions – urban (g/km)	301	
CO ₂ emissions – extra-urban (g/km)	178	
CO ₂ emissions – combined (g/km)	223	

WEIGHT AND DIMENSIONS		
Kerb weight STD. A (kg)	1.801	
Weight distribution front/rear (%)	50/50	
Max payload (kg)	437	
Height (mm) w/ standard soft top	1878	
Width (mm)	1.894	
Lenght (mm)	4.334	
Wheelbase (mm)	2.459	
Ground clearance (mm)	260	
Load capacity (I) with seats in position*	203	
Load capacity (I) with flat rear seats*	598	
*Underfloor cargo volume included		

OTHER		
Approach/departure/breakover angle	37.4/30.5/26.2	
Turning Diameter (m)	10,36	
Steering angle (inner/outer wheel)	41°/34.4°	
Steering Turns	3,68	
Steering Ratio	16.14:1	
Water fording (mm/kph)	762/8	