

	1.4 8v 70 HP	1.4 8v 78 HP	0.9 TwinAir Turbo 105 HP	1.4 TP 140 HP TCT	1.4 TP 170 HP TCT	
TECHNICAL SPECIFICATIONS						
SPECIFICATIONS	No. of cylinders, layout	4	4	2	4	
	Bore x stroke (mm)	72x84	72x84	80.5x86	72x84	
	Displacement (cm³)	1368	1368	875	1368	
	Compression ratio	11.1:1	11.1:1	10:01	9.8:1	
	Maximum power output kW (HP - EC) at rpm (NATURAL) NOR	51 (70) at 6000 rpm	57.3 (78) at 6000 rpm	72 natural (5750)/ 77 dynamic (5500)	102 (140) at 5000 rpm	125 (170) at 5500 rpm
	Peak torque Nm (kgm - EC) at rpm (NORMAL)	115 (11.76) at 3000 rpm	115 (11.76) at 3000 rpm	120 (12.2) at 1750 rpm	230 (23.4) at 2500 rpm	230 (23.4) at 2500 rpm
	Peak torque Nm (kgm-EC) at rpm (DYNAMIC)			145 (14.8) at 2000 rpm	250 (25.5) at 2500 rpm	250 (25.5) at 2500 rpm
	Fuel	Aspirated	Aspirated	ELECTRONIC INJECTION Timed sequential multipoint with knock control	Turbocharged by means of exhaust gas turbocharger with engine load management by means of variable intake valve activation	Turbocharged by means of exhaust gas turbocharger with engine load management by means of variable intake valve activation
	Stop&Start system for automatic engine stopping/starting for short stops during city driving, useful for optimising fuel consumption and CO ₂ emissions	ND	Standard	Standard	Standard	Standard
	TRANSMISSION	Drive	Front	Front	Front	Front
Transmission		Manual, 5-speed	Manual, 5-speed	Manual, 6-speed	Twin clutch	
TYRES	Standard trim level	195/55 R16	195/55 R16	195/55 R16	215/45 R17	
SUSPENSION	Front	MacPherson	MacPherson	MacPherson	MacPherson	
	Rear	Torsion beam	Torsion beam	Torsion beam	Torsion beam	
BRAKES	Front (mm)	257	257	257	305	
	Rear (mm)	251	251	251	251	
DIMENSIONS	Wheelbase (mm)	2511	2511	2511	2511	
	Length / width (mm)	4063/1720	4063/1720	4063/1720	4063/1720	
	Height (mm)	1446	1446	1446	1446	
	Track (mm)	1483/1475	1483/1475	1483/1475	1483/1475	
	Luggage compartment capacity (dm³)	270	270	270	270	
	Overhang	904	904	904	904	
CAPACITIES - WEIGHTS	Fuel tank (litres)	45	45	45	45	
	Kerb weight (kg)	1065	1070	1130	1170	
	Max. towable weight (kg) braked	500	500	500	500	
PERFORMANCE	Max. speed (km/h)	160	165	184	209	
	Acceleration (1 person + 30 kg) 0-100 km/h (s)	14	13	11.4	8.1	
	Urban cycle consumption (l/100 km)	7.6	7.3	5.0	7.0	
FUEL CONSUMPTION - EMISSIONS as per directive 1999/100/EC	Extra-urban cycle (l/100 km)	4.7	4.6	3.8	4.4	
	Combined cycle (l/100 km)	5.8	5.6	4.2	5.4	
	CO ₂ emissions (g/km)	134	130	99	124	
	Environmental classification	Euro 6	Euro 6	Euro 6	Euro 6	

1.3 JTDM 85 HP	1.6 JTDM 120 HP	1.4 TP 120 HP LPG
4	4	4
69.6x82	79.5x80.5	72x84
1248	1598	1368
16.8:1	16.5:1	9.8:1
62(85) at 3500 rpm	88 (120) at 3750 rpm	88 (120) at 5000 rpm
200 at 1500 rpm	280 (28.6) a 1500 rpm 320 (32.6) at 1750 rpm	206 (21) at 1750 rpm
Electronically controlled Common Rail Multijet direct injection with turbocharger and intercooler	Electronically controlled Common Rail Multijet direct injection with turbocharger and intercooler	Supercharged with exhaust gas turbocharger
Standard	Standard	ND
Front	Front	Front
Manual, 5-speed	Manual, 6-speed	Manual, 5-speed
195/55 R16	195/55 R16	195/55 R16
MacPherson	MacPherson	MacPherson
Torsion beam	Torsion beam	Torsion beam
281	281	281
251	251	251
2511	2511	2511
4063/1720	4063/1720	4063/1720
1446	1446	1446
1483/1475	1483/1475	1483/1475
270	270	247
904	904	904
45	45	45
1150	1205	1145 (1197)
1000	1000	500
174	198	198
12.9	9.9	8.8
4.4	5.2	10.6 / 8.2
2.9	3.7	6.6 / 5.1
3.5	4.3	8.1 / 6.2
90	112	131/145
Euro 5+	Euro 5+	Euro 6