

ALFA ROMEO **STELVIO****2.2 JTDM 210 hp
AT AWD****2.2 JTDM 190 hp
AT AWD**

SPECIFICATIONS

Fuel	Diesel	Diesel
No. of cylinders, layout	4 L	4 L
Bore x stroke (mm)	83 x 99	83 x 99
Displacement (cm ³)	2.143	2.143
Compression ratio	15,5:1	15,5:1
Max power: kW (cv-CE) @ rpm	154 (210) @ 3500	140 (190) @ 3500
Max torque: Nm (kgm-CE) @ rpm	470 (48) @ 1750	450 (46) @ 1750
Timing (control)	Belt	Belt
Fuel feed	Electronic injection	Electronic injection
Stop&Start system	Standard	Standard

TRANSMISSION

Drive	AWD	AWD
Gearbox	8 speed AT	8 speed AT
First	5,000	5,000
Second	3,200	3,200
Third	2,143	2,143
Fourth	1,720	1,720
Fifth	1,314	1,314
Sixth	1,000	1,000
Seventh	0,822	0,822
Eighth	0,640	0,640
Reverse	3,456	3,456
Final drive torque	3,270	3,270

CAPACITIES-WEIGHTS

Fuel tank (l)	58	58
AdBlue fuel tank (l)	16,1	16,1
Kerb weight (kg)	1745	1745
Kerb weight incl. driver(kg)	1.820	1.820
Max towable weight (kg) not braked	750	750
Max towable weight (kg) braked	2300	2300
Max load (kg)	2410	2410

PERFORMANCE

Top speed (km/h)	215	210
Acceleration 0-100 km/h (s)	6,6	7,6

CONSUMPTIONS' / EMISSIONS

Fuel consumption (l/100 km) urban cycle	6,5-6,9	6,5-6,9
Fuel consumption (l/100 km) extra urban cycle	5,2-5,6	5,2-5,6
Fuel consumption (l/100 km) combined cycle	5,7-6,1	5,7-6,1
CO ² emissions (g/km) combined cycle	149-160	149-160
Environmental classification	EURO 6D-TEMP	EURO 6D-TEMP

ALFA ROMEO **STELVIO****2.2 JTDM 190 hp
AT RWD****2.2 JTDM 160 hp
AT RWD**

SPECIFICATIONS

Fuel	Diesel	Diesel
No. of cylinders, layout	4 L	4 L
Bore x stroke (mm)	83 x 99	83 x 99
Displacement (cm ³)	2.143	2.143
Compression ratio	15,5:1	15,5:1
Max power: kW (cv-CE) @ rpm	140 (190) @ 3500	118 (160) @ 3750
Max torque: Nm (kgm-CE) @ rpm	450 (46) @ 1750	450 (46) @ 1750
Timing (control)	Belt	Belt
Fuel feed	Electronic injection	Electronic injection
Stop&Start system	Standard	Standard

TRANSMISSION

Drive	RWD	RWD
Gearbox	8 speed AT	8 speed AT
First	5,000	5,000
Second	3,200	3,200
Third	2,143	2,143
Fourth	1,720	1,720
Fifth	1,314	1,314
Sixth	1,000	1,000
Seventh	0,822	0,822
Eighth	0,640	0,640
Reverse	3,456	3,456
Final drive torque	3,270	3,270

CAPACITIES -WEIGHTS

Fuel tank (l)	58	58
AdBlue fuel tank (l)	16,1	16,1
Kerb weight (kg)	1660	1660
Kerb weight incl. driver(kg)	1.735	1.735
Max towable weight (kg) not braked	750	750
Max towable weight (kg) braked	1700	1700
Max load (kg)	2330	2330

PERFORMANCE

Top speed (km/h)	210	198
Acceleration 0-100 km/h (s)	7,6	8,8

CONSUMPTIONS/EMISSIONS

Fuel consumption (l/100 km) urban cycle	6,0-6,1	6,0-6,1
Fuel consumption (l/100 km) extra urban cycle	4,8-5,2	4,8-5,2
Fuel consumption (l/100 km) combined cycle	5,3-5,5	5,3-5,5
CO ² emissions (g/km) combined cycle	139-145	139-145
Environmental classification	EURO 6D-TEMP	EURO 6D-TEMP

ALFA ROMEO **STELVIO****2.0 GME 280 hp
AT AWD****2.0 GME 200 hp
AT AWD**

SPECIFICATIONS

Fuel	Petrol	Petrol
No. of cylinders, layout	4 L	4 L
Bore x stroke (mm)	84x90	84x90
Displacement (cm ³)	1.995	1.995
Compression ratio	10:01	10:01
Max power: kW (cv-CE) @ rpm	206 (280) @ 5250	148 (200) @ 4500
Max torque: Nm (kgm-CE) @ rpm	400 (41) @ 2250	330 (34) @ 1750
Timing (control)	Belt	Belt
Fuel feed	Electronic injection	Electronic injection
Stop&Start system	Standard	Standard

TRANSMISSION

Drive	AWD	AWD
Gearbox	8 speed AT	8 speed AT
First	5,000	5,000
Second	3,200	3,200
Third	2,143	2,143
Fourth	1,720	1,720
Fifth	1,314	1,314
Sixth	1,000	1,000
Seventh	0,822	0,822
Eighth	0,640	0,640
Reverse	3,456	3,456
Final drive torque	3,730	3,730

CAPACITIES -WEIGHTS

Fuel tank (l)	64	64
AdBlue fuel tank (l)		
Kerb weight (kg)	1660	1660
Kerb weight incl. driver(kg)	1.735	1.735
Max towable weight (kg) not braked	750	750
Max towable weight (kg) braked	2300	2000
Max load (kg)	2300	2300

PERFORMANCE

Top speed (km/h)	230	215
Acceleration 0-100 km/h (s)	5,7	7,2

CONSUMPTIONS' / EMISSIONS

Fuel consumption (l/100 km) urban cycle	10,0-10,2	9,8-10,0
Fuel consumption (l/100 km) extra urban cycle	6,6-6,8	6,8-7,0
Fuel consumption (l/100 km) combined cycle	7,9-8,0	7,9-8,1
CO ² emissions (g/km) combined cycle	182-186	183-187
Environmental classification	EURO 6D-TEMP	EURO 6D-TEMP

SPECIFICATIONS

Fuel	Petrol
No. of cylinders, layout	6 V
Bore x stroke (mm)	86,5 x 82
Displacement (cm ³)	2.891
Compression ratio	9,3:1
Max power: kW (cv-CE) @ rpm	375 (510) @ 6.500
Max torque: Nm (kgm-CE) @ rpm	600 (61) @ 2.500
Timing (control)	Chain
Fuel feed	Electronic injection
Stop&Start system	Standard

TRANSMISSION

Drive	AWD
Gearbox	8 speed AT
First	5,000
Second	3,200
Third	2,143
Fourth	1,720
Fifth	1,314
Sixth	1,000
Seventh	0,822
Eighth	0,640
Reverse	3,456
Final drive torque	3,700

CAPACITIES -WEIGHTS

Fuel tank (l)	64
AdBlue fuel tank (l)	
Kerb weight (kg)	1830
Kerb weight incl. driver(kg)	1.905
Max towable weight (kg) not braked	-
Max towable weight (kg) braked	-
Max load (kg)	2.460

PERFORMANCE

Top speed (km/h)	283
Acceleration 0-100 km/h (s)	3,8

CONSUMPTIONS'/EMISSIONS

Fuel consumption (l/100 km) urban cycle	12,3
Fuel consumption (l/100 km) extra urban cycle	8,4
Fuel consumption (l/100 km) combined cycle	9,8
CO ² emissions (g/km) combined cycle	227
Environmental classification	EURO 6D-TEMP