

ENGINE	Wrangler Rubicon 2-door petrol 3.6 ATX 4WD 285 hp
No. of cylinders, layout	6 – in line
Displacement (cm ³)	3605
Bore x stroke (mm)	96.0 x 83.0
Valves per cylinder	4
Compression ratio	11.3:1
Max. power kW @ rpm	209 kW @ 6.400
Max. torque Nm @ rpm	347 Nm @ 4.100
Fuel injection	Port fuel Injected
Fuel type	Petrol
Fuel tank capacity (l)	66
GEARBOX	
Transmission	8-speed AUTOMATIC
1 st	4.714
2 nd	3,143
3 rd	2.106
4 th	1.667
5 th	1.285
6 th	1.000
7 th	0.839
8 th	0.667
Reverse	3.295
Final drive ratio	4.1
DRIVETRAIN	
Transfer case	Rock-Trac Low gear 4.0:1
Crawl ratio	77.2

PERFORMANCE	
Acceleration: 0-100 kph (s)	-
Top Speed (kph)	156
CONSUMPTION AND EMISSIONS	
Emission standard	EU6B
Fuel consumption – urban (l/100 km)	13.5
Fuel consumption – extra-urban (l/100 km)	8.2
Fuel consumption – combined (l/100 km)	10.1
CO ₂ emissions – urban (g/km)	313
CO ₂ emissions – extra-urban (g/km)	190
CO ₂ emissions – combined (g/km)	235

WEIGHT AND DIMENSIONS	
Kerb weight STD. A (kg)	1890
Weight distribution front/rear (%)	50/50
Max payload (kg)	439
Height (mm) w/ standard soft top	1879
Width (mm)	1.894
Lenght (mm)	4.334
Wheelbase (mm)	2.459
Ground clearance (mm)	255
Load capacity (l) with seats in position*	203
Load capacity (l) with flat rear seats*	598
<i>*Underfloor cargo volume included</i>	

OTHER	
Approach/departure/breakover angle	36.4/30.8/25.85
Turning Diameter (m)	10,36
Steering angle (inner/outer wheel)	41°/34.4°
Steering Turns	3,68
Steering ratio	16.14:1
Water fording (mm/kph)	762/8