ENGINE	Wrangler Sahara 4-door petrol 3.6 ATX 4WD 285 hp
No. of cylinders, layout	6 – in line
Displacement (cm ³)	3605
Bore x stroke (mm)	96.0 x 83.0
Valves per cylinder	4
Compression ratio	11.3:1
Max. power kW @ rpm	209 kW @ 6400
Max. torque Nm @ rpm	347 Nm @ 4100
Fuel injection	Port fuel Injected
Fuel type	PETROL
Fuel tank capacity (l)	81
GEARBOX	
Transmission	8-speed AUTOMATIC
1 st	4.714
2 nd	3,143
3 rd	2.106
4 th	1.667
5 th	1.285
6 th	1.000
7 th	0.839
8 th	0.667
Reverse	3.295
Final drive ratio	3.45
DRIVETRAIN	
Transfer case	Command-Trac Low gear 2.72:1
Crawl ratio	44.2

PERFORMANCE		
Acceleration: 0-100 km/h (s)	-	
Top Speed (km/h)	177	
CONSUMPTION AND EMISSIONS*		
Emission standard	EU6B	
Fuel consumption – urban (I/100 km)	13	
Fuel consumption – extra-urban (l/100 km)	7.8	
Fuel consumption – combined (l/100 km)	9.7	
CO ₂ emissions – urban (g/km)	302	
CO ₂ emissions – extra-urban (g/km)	180	
CO ₂ emissions – combined (g/km)	225	

WEIGHT AND DIMENSIONS		
Kerb weight STD. A (kg)	1934	
Weight distribution front/rear (%)	52/48	
Max payload (kg)	451	
Height (mm) w/ standard soft top	1891	
Width (mm)	1.894	
Lenght (mm)	4.882	
Wheelbase (mm)	3.008	
Ground clearance (mm)	242	
Load capacity (I) with seats in position*	548	
Load capacity (I) with flat rear seats*	1059	
*Underfloor cargo volume included		

OTHER		
Approach/departure/breakover angle	35.4/30.7/20.0	
Turning Diameter (m)	12,28	
Steering angle (inner/outer wheel)	41°/34.4°	
Steering Turns	3.24	
Steering Ratio	14.2	
Water fording (mm/kph)	762/8	